<u>probst</u>



STS-43-EH-23

STONE SPLITTER STS-43-EH-23 **Electro-hydraulic block splitter**



Snap electrohydraulically at the touch of a button - entirely without dust, noise or wastewater. The environmentally friendly alternative to block sawing.

Splitting of stones at the push of a button. Rigidly mounted, split triangular reversible blade made of hardened metal, for e.g. granite stones, max. height difference 4 mm, minimum stone length 180 mm. Due to the inclined support tables a clean undercut is possible, for exact placement without large distances.

- Integrated rechargeable battery.
- High splitting force of 23 tonnes.
- Integrated scale for adjusting the cutting height via crank.
- Large wheels for easy manoeuvring on uneven terrain.
- Folding handle for easy moving by hand.
- Suspension eye for transport with a crane or lifting device.
- Battery monitor for checking the charge status.
- 4 handles for easy manoeuvering.
- One side of the support table can be altered for precise undercutting.



Туре	Width Cutting Width mm (in)	Dead Weight kg (lbs)	Height Stone/Element mm (in)	Force Splitting Force kg(daN)	Order - Number
STS-43-EH-23	430 (16.93)	170 (375)	10 - 220 (0.39 - 8.66)	23,000	51200081

Accessories:

Туре	Description	Order-Number
LG-220 V/12V	Battery charging device w/overload protection and charging current limiting. Housing is water and dust-proof	24200152



Radial Cut Adapter RSA



- The RSA converts each standard block cutter into a radial cutter within seconds.
- Now concrete pavers can also be cut with a radius. So connections around manhole covers can be done precisely, quickly and professionally with-out breaking the optics.
- Suitable for outside diameter of manhole covers of approx. 700 800 mm (27.55 31.49 inch).
- Easy handling, RSA has only to be positioned between the two plates of the cutter. The RSA does not have to be rigidly fixed in this position.
- Durable surface protection by galvanizing.

Туре	Width Cutting Width mm (in)	Width mm (in)	Dead Weight kg (lbs)	Height Stone/Element mm (in)	Order-Number
RSA-25	250 (9.84)	355 (13.98)	4.36 (9.61)	50 – 100 (1.97 – 3.94)	41200016