



Lifting Hose Units HE

For use with the JUMBOMOBIL JM, JUMBO-BV, TRANSMOBIL TM, JUMBO Travelling Crane JWK or on any other crane carrier.

(Application of lifting hose unit HE-250 is not to be operated and JUMBOMOBIL).

Consists of:

Transportation hook.

Rotational Device and quick coupling, 2 inch.

Lifting hose unit with protective fabric as well as a flange for fitting onto the operating valve unit.

Available optionally for HE-150/200/250: reinforced belt stay with buckle.

HE-35 – HE-250

5

Type	Diameter outside mm (in)	Dead Weight kg (lbs)	Height Lifting Height mm (in)	Working Load Limit/WLL -420 mbar kg (lbs)	Order-Number
HE-35	120 (4.72)	9.5 (21)	1,700 (66.93)	35 (77)	42100001
HE-50	140 (5.51)	10.5 (23)	1,700 (66.93)	50 (110)	42100106
HE-85	178 (7.01)	13.5 (30)	1,700 (66.93)	85 (187)	42100002
HE-150	230 (9.06)	18.5 (41)	1,500 (59.06)	150 (331)	42100132
HE-200	250 (9.84)	22.5 (50)	1,500 (59.06)	200 (441)	42101114
HE-250	300 (11.81)	26.6 (59)	1,500 (59.06)	250 (551)	42101115



Operating Valve Unit BE-SPRINT-2

For direct coupling onto the lifting unit HE.

Longer operating handles on request.

Main body with handle 500 mm (19.68 inch) long, fixing screw for adjusting the hovering position, safety gauge.



BE-SPRINT-2

Type	Description	Dead Weight kg (lbs)	Order-Number
BE-SPRINT-2	for HE-35 up to HE-250	8.5 (19)	42100539