

Type	Description	Dimensions L x W mm (in)	Type of Drive electric/AC (60 Hz) kW	Type of Drive electric/AC (50 Hz) kW	Electric Voltage /AC (50 Hz) V	Electric Voltage /AC (60 Hz) V	Dead Weight kg (lbs)	Working Load Limit/ WLL -200 mbar kg (lbs)	Order-Number
VS-140/200	incl. suction plate 50 kg (110 lbs)	300 x 250 (11.81 x 9.84)		1.5	230		24 (53)	200 (441)	52700015
VS-140/200-XL	incl. suction plate 50 kg (110 lbs) with long handle and lifting eye	300 x 250 (11.81 x 9.84)		1.5	230		30 (66)	200 (441)	52700016
VS-140/200-110	incl. suction plate 50 kg (110 lbs)	300 x 250 (11.81 x 9.84)	1.5			110	24 (53)	200 (441)	52700019
VS-140/200-XL-110	incl. suction plate 50 kg (110 lbs) with long handle and lifting eye	300 x 250 (11.81 x 9.84)	1.5			110	30 (66)	200 (441)	52700020

Accessories:

Type	Description	Dead Weight kg (lbs)	Working Load Limit/WLL kg (lbs)	Order-Number
VS-EH	Lifting eye with safety chain for VS-140 and VS-140/200	3.74 (8.25)	200 (441)	42710143
VS-140-XL-HG	Pair of long handles for VS-140/200 for slabs up to 1,2 m width	9 (20)	140 (309)	42710089



VS-PR

SPEEDY POWER-RACK VS-PR

Holder for practical storing of the EU 22i Honda generator when operating the SPEEDY on lifting equipment (e.g. a digger).

- VS-PR is simply hung on the carrying device with adjusted generator (not included in the scope of delivery).
- The VS-EH (not included in the scope of delivery) lifting eye of the SPEEDY is then hung on the eye hook of the VS-PR.
- In the case of a carrying device with a large lifting height, the eye hook may be connected to the VS-EH lifting eye with the 2 m long loop supplied. Thus, first the SPEEDY then the VS-PR can be switched off.
- Incl. 3 m/118 inch (extension cable + Velcro strap.
- Durable surface protection by galvanizing.



Type	Dead Weight kg (lbs)	Working Load Limit/WLL kg (lbs)	Order-Number
VS-PR	10 (22)	200 (441)	42710166