# probst





SH-2500-GREENLINE

## **Vacuum Lifting Device SH-2500-GREENLINE**

max. 2,500 kg/5,500 lbs

#### The classic now also with battery power. Powerful and independent of mains power.

Suitable for predominantly non-porous concrete and natural stone elements.

Fitted as standard with load securing chain.

Powered by a 24 V lithium-ion rechargeable battery. (exchangeable battery concept) can operate up to 6 hours.

Can be equipped with a hydraulic rotator as an add-on if requested.

■ Emission-free and low-noise operation.

### Scope of delivery:

SH-2500-GREENLINE: 1 x Lithium-ion battery and a 230 V/50 Hz charger. The charging time is approx. 2.5 hours.

SH-2500-GREENLINE-FFS: As SH-2500-GREENLINE, but with additional remote control for suction and release.

Туре	Description	Battery Capacity Ah	Type of Drive electric/Battery kW	Working Voltage V	Dead Weight kg (lbs)	Working Load Limit/WLL -600 mbar kg (lbs)	Order-Number
SH-2500- GREENLINE	Basic device, without suction plate	23	0.4	24	151 (333)	2,500 (5,512)	52400046
SH-2500- GREENLINE-FFS	Basic device, without suction plate. With remote control	23	0.4	24	151 (333)	2,500 (5,512)	52400048

#### **Accessories:**

SH-2500-HGV: Should be used when laying elements wider than 1 meter (39.37 inch). This way, the employee is out of the danger zone during the application. Handle Extension SH-2500-HGV can be fitted at any time later to the structure of SH-2500 by bolting it on with brackets. SH-2500-RS: The wheelset consists of two attachable main wheels, diameter 300 mm (11.81 inch), one support-wheel and one swivelling wheel. Later attachment to the basic device SH is no problem.

Туре	Description	Battery Capacity Ah	Working Voltage V	Dead Weight kg (lbs)	Order-Number
Lithium-ion battery- 24V/23Ah	Spare storage battery for SH-2500-GREENLINE	23	24	5 (11)	24200142
SH-2500-HGV	Handle extension for all models SH-2500			5.5 (12)	42400088
SH-2500-RS	Wheelset for all models SH-2500			7.7 (17)	42500299

For suction plates see page 97.

