



1



VTK-V with supporting wheel



VTK-V with AR

## Adjustable Paver Transport Cart VTK-V

For the effortless transportation of bound or loose pavers, kerb stones, slabs, etc.

Clamping is done by operating a lever 90° (maximum pressure 15 kg).

Adjustable gripping width from 550 mm – 1,050 mm.

- An integral protection device prevents overloading of the clamping mechanism.
- A favourable load distribution and the light-weight-nature of the device ensures optimal operating.
- Its narrow build means it can be used on the smallest building sites.
- Blocks can easily be loaded from the pallet without the need of a ramp.
- Fully mechanical.
- Adjusts smoothly and without the need for tools.
- Durable galvanized surfaces.

Type	Length of Gripper mm (in)	Dead Weight kg (lbs)	Height Stone/ Element mm (in)	Clamping Range mm (in)	Working Load Limit/ WLL kg (lbs)	Order-Number
<b>VTK-V</b>	200 (7.87)	68 (150)	900 (35.43)	550 – 1,050 (21.65 – 41.34)	400 (882)	<b>51100015</b>

### Accessories:

Type	Description	Dimensions L x W x H mm (in)	Dead Weight kg (lbs)	Order-Number
<b>VTK-V-AR</b>	Access ramp for VTK-V, to make picking up interlocking paving stones on the pallet easier. L = 700 mm (27½ in), W = 850 mm (33½ in), H = 160 mm (6¼ in)	700 x 850 x 160 (27.56 x 33.46 x 6.30)	10 (22)	<b>51100014</b>
<b>VTK-V-SR/N</b>	Supporting wheel for easy handling on even ground. Can be additionally attached at any time.		7 (15)	<b>41100041</b>