



Fork Lift Grab STAZ-UNI-4

Specially designed for the safe gripping of un-strapped and un-compressed stacks of multilayer production.

The same characteristics as the STAZ-UNI but equipped with a four-sided clamping action.

Because the main and the end gripping is hydraulically controlled separately, and by using pressure plates (accessory), an exact Two compression of the stacks and the elimination of any gaps are achieved

Separate hydraulic circuits are neccessary to be supplied by the fork lift truck.

(Supplied without connecting hoses to the fork lift truck).

Required jaw lengths depending on the dimensions of the stone layer.

Contoured grippers for special layers on special request.

STAZ-UNI-4 + fork sleeve + pressure plates

Туре	Inside Height mm (in)	Dead Weight kg (lbs)	Hydraulic Connection Pressure bar (psi)	Opening Width Side Gripper mm (in)	Opening Width Main Gripper mm (in)	Working Load Limit/ WLL kg (lbs)	Order-Number
STAZ-UNI-4-850	850 (33.46)	765 (1,687)	180 - 210 (2,611 - 3,046)	900 - 1,400 (35.43 - 55.12)	550 - 1,230 (21.65 - 48.43)	3,000 (6,614)	57000165
STAZ-UNI-4- 1000	1,000 (39.37)	810 (1,786)	180 - 210 (2,611 - 3,046)	900 - 1,400 (35.43 - 55.12)	550 - 1,230 (21.65 - 48.43)	3,250 (7,165)	57000166
STAZ-UNI-4- 1200	1,200 (47.24)	940 (2,072)	180 - 210 (2,611 - 3,046)	900 - 1,400 (35.43 - 55.12)	550 - 1,230 (21.65 - 48.43)	3,500 (7,716)	57000167



Selective Layer Clamp STAZ-SLC

Specially designed to help select one or several layers of stones with a fork lift truck.

Without connecting hoses to the fork lift truck, without fork sleeves and without rubber grippers, see accessories.

- Manually adjustable pressure relieve valve.
- Oil Pressure Gauge.
- Has an integrated, adjustable height stop, controlled by the gripping function, only one hydraulic circuit is necessary.
- Adjustable height stop is being controlled by a scissor system it therefore reduces the necessary space required.
- Low maintenance Steel-Plastic-Sliding Guide.

Туре	Inside Height mm (in)	Dead Weight kg (lbs)	Hydraulic Connection Pressure bar (psi)	Opening Width Main Gripper mm (in)	Working Load Limit/WLL kg (lbs)	Gripper Base Length Main Gripper mm (in)	Order-Number
STAZ-SLC	500/700 (19.69/27.56)	367 (809)	180 - 210 (2,611 - 3,046)	370 - 1,370 (14.57 - 53.94)	1,500 (3,307)	1,250 (49.21)	57050034