

Type	Length of Gripper mm (in)	Diameter outside mm (in)	Inside Height mm (in)	Dead Weight kg (lbs)	Gripping Range mm (in)	Working Load Limit/WLL kg (lbs)	Order-Number
ASZ	200 (7.87)		120 (4.72)	26 (57)	600 – 1,200 (23.62 – 47.24)	250 (551)	53100259-005
A-50	50 (1.97)			1.3 (2.87)			43100376
A-100	100 (3.94)			0.8 (1.76)			43100377
ASZ-R	300 (11.81)	600 – 1,200 (23.62 – 47.24)	100 (3.94)	34 (75)		250 (551)	53100281-003



### Pneumatic Rotating Clamp P-WG

For rotation by 90° or 180° of concrete products as for example slabs, side-angles, kerb stones.

Pneumatic clamping and rotating around the longitudinal axis.

- Lifting eye for attaching to crane hook.
- Pneumatic closing cylinder and additional manual adjustment for a larger opening width.
- Manual-controlled valves for clamping and rotating at the guide handle.
- Grippers coated with exchangeable rubbers.

P-WG

Type	Compressed Air Connection Pressure bar (psi)	Inside Height mm (in)	Dead Weight kg (lbs)	Opening Width Main Gripper mm (in)	Working Load Limit/ WLL kg (lbs)	Angle Pivoting-/ Rotation Angle ° Degree	Order-Number
P-WG	6 – 10 (87.02 – 145.04)	285 (11.22)	200 (441)	600 – 2,000 (23.62 – 78.74)	500 (1,102)	180	57400109



### Pneumatic Sorting Clamp ASZ-P

This universal outsourcing clamp offers a versatile use due to large adjustable opening width. Optimum for slabs, kerb stones and wall-rings for plants, etc.

Suitable for attachment to a vacuum lifting unit or to a overhead or jib crane.

Cylinder lifting 150 mm (6 inch): the further range of opening width is mechanically adjustable.

- With flange plate to attach to a vacuum lifting unit, alternatively with a lifting eye.
- With pneumatic closing cylinder and additional manual adjustment to achieve a larger opening width.
- Hand-guided valve with closing cylinder.
- Other opening widths and heights are available on request.

ASZ-P

Type	Compressed Air Connection Pressure bar (psi)	Dead Weight kg (lbs)	Opening Width Main Gripper mm (in)	Working Load Limit/WLL kg (lbs)	Order-Number
ASZ-P	6 – 10 (87.02 – 145.04)	32 (71)	220 – 1,050 (8.66 – 41.34)	120 (265)	57400023

011223 Technical data contained in this catalogue can be modified without prior notice in the interest of progress. Illustrations are exemplary and non-binding. No liability accepted for any misprints, mistakes and errors.