## PaverEXTRACTOR / Paving Block Extractor SZ

The professional's answer to paver removal. Serrated spring steel teeth extract a large variety of pavers, including ones without spacer bars. Removing pavers with a PaverEXTRACTOR saves time and protects the surrounding pavers. Save time and money with the right tool for the job.

- Quick pin for fast adjustments
- Replaceable serrated spring steel teeth
- Zinc plated
- Opening Range: 3-13 in (9-33 cm)

## Pro Tip: After using water as lubricant, use putty knife to loosen & remove poly sand first.

Туре	Opening Range in (mm)	Dead Weight Ibs (kg)	Order-Number
PaverEXTRACTOR	3-13 (90-330)	9 (4)	51800030
Extractor Replacement Blade	-	2 (.9)	41800001









## **SlabEXTRACTOR<sup>™</sup> / Slab Extractor PZ**

- Two person slab removal
- Quick pin for fast adjustment
- Uses four extractor teeth
- Opening Range: 5"- 24" (13 61 cm)
- Lifting Capacity: 150 lb (68 kg)

Туре	Opening Range in (cm)	Dead-Weight Ibs (kg)	Order- Number
SlabEXTRACTOR	5 - 24 (13 - 61)	13 (6)	53200006
Extractor Replacement Blade	-	2 (.9)	41800001

2